

Electronic Universal Ballasts



Ideal for industrial and commercial lighting applications, MaxLite's High Efficiency Ballasts provide power for 2-, 3- and 4-lamp fixtures for linear, PL, and U lamps. Available with universal voltage, anti-striation and high-efficiency models and nominal, low and high output styles, the ballasts operate on universal 120- and 277-VAC electrical systems.

FEATURES:

- Industry leading rate of less than 500 parts per million
- Instant start/ programmable
- Nominal/ high/ low output
- 2 lamp/ 3 lamp/ 4 lamp
- PL replacement ballasts
- 5 year limited warranty

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE



Category	Lamp Type	Watts	# of Lamps	Order Code	Model Number	Line Volts (V)	Input Wattage	Input Current	Ballast Factor	Case Pack	Tech.	Foot Print L"xW"xH"	(Box) Weight (lbs.)
Normal Ballast Factor T8	F32	32	2	70419	SKEU1322/SC	120	57	0.49	0.88	20	Instant	9.5x1.3x1	1.10
	F32	32	2	70420	SKEU322/SC	120-277	59	0.50/0.21	0.88	20	Instant	9.5x1.3x1	0.99
	F32	32	2	70524	SKEU322HE/SC	120-277	55/54	0.46/0.20	0.88	20	Instant	9.5x1.3x1	0.99
	F32	32	3	70538	SKEU323/SC	120-277	85	0.71/0.31	0.88	20	Instant	9.5x1.3x1	1.12
	F32	32	4	70488	SKEU324/SC	120-277	112/108	0.94/0.40	0.88	20	Instant	9.5x1.3x1	1.13
	F32	32	4	70526	SKEU324HE/SC	120-277	110/108	0.94/0.40	0.88	20	Instant	9.5x1.3x1	1.18
	F32	32	4	70587	SKEU1324/SC	120	112	0.93	0.88	20	Instant	9.5x1.3x1	1.14
	F96	59	2	70491	SKEU962/SC	120-277	108/106	0.92/0.40	0.88	20	Instant	9.5x1.3x1	1.01
High Ballast Factor T8	F32	32	2	70484	SKEU322HEH/SC	120-277	76/75	0.64/0.27	1.19	20	Instant	9.5x1.3x1	0.99
	F32	32	3	70522	SKEU323H/SC	120-277	109/107	0.91/0.39	1.22	20	Instant	9.5x1.3x1	1.12
	F32	32	4	70489	SKEU324H/SC	120-277	145	1.24/0.53	1.22	20	Instant	9.5x1.3x1	1.58
	F32	32	4	70485	SKEU324HEH/SC	120-277	145/144	1.24/0.53	1.22	20	Instant	9.5x1.3x1	1.06
	F32	32	4	70587	SKEU1324/SC	120	112	0.93	0.88	20	Instant	9.5x1.3x1	1.14
	F32	32	4	70527	SKEU324HEL/SC	120-277	98/96	0.82/0.35	0.77	20	Instant	9.5x1.3x1	1.00
Low Ballast Factor T8	F32	32	2	70525	SKEU322HEL/SC	120-277	48/47	0.40/0.17	0.77	20	Instant	9.5x1.3x1	0.99
	F32	32	2	70421	SKEU322L/SC	120-277	48	0.44/0.19	0.78	20	Instant	9.5x1.3x1	0.99
	F32	32	3	70539	SKEU323L/SC	120-277	76/74	0.64/0.27	0.77	20	Instant	9.5x1.3x1	1.12
	F32	32	4	70490	SKEU324L/SC	120-277	98/96	0.82/0.35	0.77	20	Instant	9.5x1.3x1	1.17
Low Ballast Factor T8	F54	54	2	70492	SKEU542HOP/SC	120-277	120/117	1.00/0.43	1	20	Program Rapid Start	9.5x1.3x1	1.10
	F54	54	2	70852	SKEU544HOP/SC	120-277	240/234	0.50/0.21	1	20	Program Rapid Start	16.7x1.7x1.2	2.50

Note: All of our T8 ballasts operate multiple lamp wattages and quantity of lamps. Refer to the data sheet at <http://www.maxlite.com/products/ballasts> for a complete listing of lamp types that correspond with the quantity of lamps per ballast and other necessary specs.

