

# GU24 OMNIDIRECTIONAL A19 LED LAMP



MaxLite's LED GU24 Omni A19 lamp is the most versatile light source in the market. It replicates a true A19 incandescent replacement lamp with a 300-degree beam angle that produces even light from the socket base and above in all directions. The 10-watt GU24 lamp emits light equivalent to a 60-watt incandescent bulb respectively. MaxLED's® LED Omni A19 Lamps can yield up to 85 percent savings in energy. Lumen maintenance is maximized by using a multi layer tapered heat sink.

PROJECT NAME

CATALOG NUMBER

NOTES

FIXTURE  
TYPE

## FEATURES:

- 3000K & 4000K CCT
- 35,000 hour life (L70 standards)
- Proprietary housing for thermal heat protection
- CRI: 80
- Five year limited warranty
- Dimmable down to 10 percent
- Saves up to 90 percent on energy and operating costs
- Power factor: > .9
- Not for use in totally enclosed luminaires

## APPLICATIONS:

- Ceiling fixtures
- Chandeliers
- Pendants
- Table and floor lamps
- Sconces

## CONSTRUCTION:

**LEDs:** All LEDs are matched for color and CRI. The stated 35,000 hour life is based on functional light quality. After 70 percent lumen depreciation, MaxLite considers the functional life of the lamp to be ended.

**Housing:** The body of each lamp is constructed of aluminum and plastic materials. The tiered heat sink promotes heat dissipation and features a tapered look. This keeps the LED junction temperature well below the manufacturer's specification. The lamp stays cool and the lumens are maintained for longer life.

**Base:** The Omni A19 bulb has a GU24 base.

### Lamp Ordering Information:

Watts	Order Number	Model Number	Delivered Lumens	Beam	Lamp Life (Hrs.)	Dimensions	CCT
10	72063	SKBO10GUDLED30	780	300°	35,000	2.45" x 4.43"	3000
10	72215	SKBO10GUDLED40	800	300°	35,000	2.45" x 4.43"	4000

MAX13003



Lighting layouts and spacing criteria available upon request



# GU24 OMNIDIRECTIONAL A19 LED LAMP

## DIMENSIONS:



## COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL
Lutron	TG-600PR-IV
Lutron	S-600PR-WH
Lutron	CT-103P
Leviton	cat.NO.6683-P