

CFL PARs & Rs



Compact Fluorescent Flood Lamps

Designed to replace 30- to 125-watt incandescent bulbs used in recessed cans and track lighting in homes, offices, restaurants, schools, hospitals, and retail and hospitality applications, MaxLite's 7- to 23-watt compact fluorescent lamps (CFL) PARs and Rs save up to 75 percent in energy costs over incandescent bulbs, while maintaining the same size and shape. Suitable for both indoor and outdoor uses, MaxLite's CFL PARs and Rs are available in 2700K (warmer white), 3000K (warm white) 4100K (cool white) and 5000K (daylight) correlated color temperatures (CCT). and ENERGY STAR®-rated models.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

FEATURES:

- Fits flush with standard recessed can fixtures
- Long life – lasts up to 10,000 hours
- Saves up to 75 percent in energy costs
- Same size and shape as incandescent lamps
- PAR lamps are suitable for indoor/outdoor use
- Frosted glass on R20, R30 and R40 for softer light

Specification:

- Ballast Type: Electronic
- Starting Method: Instant Start
- Input Line Voltage: 120VAC
- Input Line Frequency: 50/60HZ
- Min. Starting Temperature: 0°F
- Max. Operating Temp.: 100°F
- CRI: 84



R Lamp Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Initial Lumens	Pack Type (Case Pack)	Life (Hrs.)	Dimensions (W"xH")	CCT
7	07007	SKR207FLWW	30	245	Box (25)	8,000	2.5 x 4.6	2700
11	07011	SKR211FLWW	30	300	Box (25)	8,000	2.5 x 4.6	2700
* 15	33015	SKR315FLWW-107	75	750	Box (12)	10,000	3.7 x 5.6	2700
* 15	33031	SKR315FLCW	75	550	Box (12)	10,000	3.7 x 5.6	4100
15	33019	SKR315FLDL	75	600	Box (12)	10,000	3.7 x 5.6	5000
* 15	70811	MLR315FLWW	75	750	Box (12)	10,000	3.75 x 5.4	2700
23	70728	SKR4023FLWW	125	1100	Box (12)	10,000	4.9 x 6.3	2700
23	33030	SKR423FLCW	125	1200	Box (12)	10,000	4.9 x 6.3	4100
23	70282	SKR423FLDL	125	1200	Box (12)	10,000	4.9 x 6.3	5000
* 23	33023	SKR423FLWW-155	125	1200	Box (12)	10,000	4.75 x 6.2	2700
* 23	33028	SKR423FLWW-107	125	1300	Box (12)	10,000	4.8 x 6.3	2700

PAR Lamp Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Initial Lumens	Pack Type (Case Pack)	Life (Hrs.)	Dimensions (W"xH")	CCT
* 9	11197	SKR2009FLWW	30	300	Box (12)	8,000	2.45 x 3.8	2700
9	11199	SKR2009FLDL	30	300	Box (12)	8,000	2.45 x 3.8	5000
9	70279	SKR2009FLCW	30	300	Box (12)	8,000	2.45 x 3.8	4100
* 15	70819	SKPAR3015WW-136	75	700	Box (12)	10,000	3.7 x 4.8	2700
15	71833	SKPAR3015CW-136	75	720	Box (12)	10,000	3.7 x 4.8	4100
15	71883	SKPAR3015DL-136	75	700	Box (12)	10,000	3.7 x 4.8	5000
* 20	33032	SKR3820FLWW	75	900	Box (12)	8,000	4.8 x 6.5	2700
* 23	33016	SKR3823FLWW-156	100	1300	Box (12)	10,000	4.8 x 5.3	2700
* 23	11150	SKR3823FLDL-156	125	1200	Box (12)	10,000	4.8 x 5.3	5000

* ENERGY STAR Qualified

MAX12152

CFL PARs & Rs

Compact Fluorescent Flood Lamps



PERMA DISK PAR Lamp Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Initial Lumens	Pack Type (Case Pack)	Life (Hrs.)	Dimensions (W"xH")	CCT
9	11382	SKR2009FL30PD	30	350	Box (12)	8,000	2.45 x 3.8	3000
15	33033	SKR3015FL30PD	75	750	Box (12)	8,000	3.75 x 5.1	3000
18	11189	SKR3818FLWWPD	100	1200	Box (12)	8,000	5 x 6.2	2700
23	33034	SKR3823FL30PD	100	1200	Box (12)	8,000	5 x 6.2	3000



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.

