

MLCAN60LED50

60W LED CANOPY AND GARAGE LIGHT



Surface mounted Canopy and garage fixture. Shatter and UV resistant polycarbonate lens.

LED System: Uses proprietary binning for color consistency. Highlighting a 98% power factor and 120° beam angle LED.

Fixture can be mounted to electrical box or mount direct to surface.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

FEATURES:

- Replaces up to 250 Watt Metal Halide
- Lumens delivered 3945
- 61.4 Watts
- 5000K
- 50,000 hour life at L70 standards
- Self-contained driver
- Universal 120V through 277V
- Maintenance free; no UV
- Dusk To Dawn / Occupancy sensor compatible
- Can mount on electrical box or direct to surface
- LM-79/80 data available
- 5 Year Limited Warranty
- 20- and 40W model available
- Does not attract insects



CONSTRUCTION:

Fixture: Heavy-duty cast aluminum one-piece housing; polyester powdercoat; rust and corrosion proof. Fixture is sealed to be dirt and bug proof.

Lens: High quality shock proof polycarbonate lens with UV inhibitors

LED Module: Copper plating to provide high thermal transfer rate minimizing junction temperature of LED to maximize service life.



Luminaire Ordering Information:

WATTS	ORDER CODE	MODEL NUMBER	LUMENS	LAMP LIFE (Hrs)	DIMENSIONS (L"xW"xH")	K
61.4	71518	MLCAN60LED50	3945	50,000	12.25 x 12.25 x 9.0	5000
61.4	71517	MLCAN60LED50W	3945	50,000	12.25 x 12.25 x 9.0	5000

MAX12091-4-02

Lighting layouts and spacing criteria available upon request

SPECIFICATIONS:

Item	Specification	Details
General Performance	Spacing Criteria	Available upon request
	Color Temperature	5000K
	Lumens	3945
	Efficacy	64.3 lumen/watt
	Color Consistency	Proprietary binning for uniform color
	Lumen Maintenance (L70)	50,000 hours
Electrical	Power Factor	Over 98%
	Input Voltage	120V-277V 50/60 Hz
	Power Consumption	61.4 Watts
Physical	Dimensions	12.25" x 12.25" x 9.0"
	Weight	8.8 lbs
	Housing	Aluminum
	Lens	Shock proof polycarbonate
	Mounting	Fits electrical box or mount direction surface
	Operating Temperature	-30°F to 130°F
	Humidity	20% - 85% RH, non condensing
Certification	Certification	ETL, FCC, LM80
	Material Usage	RoHS compliant; no mercury
	Environment	Indoor / Outdoor
	LED Class	L70 rated to 50,000 hours

Lighting layouts and spacing criteria available upon request

DIMENSIONS:

