

MLHMXTL

100W, 150W, and 200W HIGHMAX TEMPORARY WORK LIGHT & FIXTURE

A Temporary Work Light fixture, with a mogul base for 100-, 150-, and 200 watt HighMax high lumen output lamps. Available for 120 or 277 volt electrical systems, the fixture comes with a hook and can be hard-wired, or supplied with a cord and plug. The lamp is self-ballasted, so no additional ballast required.

The chrome-plated steel wire guard provides complete protection for the lamp, and enables full light distribution.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

FEATURES:

- Guard is chrome-plated steel
- Socket is mogul base
- Comes with hook; cord and plug available
- Operates on universal 120 or 277 volt electrical systems
- 3 wattages to choose from: 100, 150, and 200
- CRI: 84
- Lamps are self-ballasted (no external ballast required)
- 10,000 hours life
- 1 year limited warranty on lamps



MOUNTING OPTIONS:

Die cast aluminum safety-hook, in a 2/3" threaded conduit hub. Fixture can be direct wired, or a 6' SOW16/3 cord and plug can be ordered. HighMax lamps screw-in to mogul socket.

HIGHMAX LAMPS:

The HighMax lamps supplied offer a high lumen output in a mogul base socket. Lamps are self-ballasted with long life of 10,000 hours, and available in 5000K (daylight) color temperature and a CRI of 84.

HIGHMAX TEMPORARY WORK LIGHT & FIXTURE SPECIFICATIONS

WATTS	ORDER CODE	MODEL NUMBER	VOLTAGE	HID EQUIVALENT	LAMP LIFE (Hrs.)	LUMENS	CCT
200	70835	SK200TL27750	277	400	10,000	12,000	5000
200	70836	SK200TL12050	120	400	10,000	12,000	5000
150	70837	SK150TL12050	120	250-400	10,000	9,200	5000
150	70838	SK150TL27750	277	250-400	10,000	9,200	5000
100	70839	SK100TL12050	120	400	10,000	6,900	5000
100	70840	SK100TL27750	277	400	10,000	6,900	5000

Lighting layouts and spacing criteria available upon request