

PRODUCT FOCUS

True 2700K
Color

LED

Energy Saving Lamps

- FOR >> CHANDELIERS**
 >> MULTI-SOCKET FIXTURES (MARQUEES)
 >> SIGNAGE
 >> WALL SCONCES
 >> WALL WASHING



SKCT2.2WWLED



SKCD2.2WWLED



SKGC2.2WWLED



SKRF2.2WWLED



SKGCC2.2WWLED

- True 2700K Color
- Super Long Life- 50,000 Hours
- 5 Year Warranty
- Available in clear frosted and faceted glass
- Decorative shape and ultra-small size
- Very low maintenance cost

PRODUCT FOCUS

LED

Energy Saving Lamps



SKCT2.2WWLED
50,000 Hour
(7) 676271191 (4)*



SKCD2.2WWLED
50,000 Hour
(7) 6762711204 (1)*



SKGC2.2WWLED
50,000 Hour
(7) 6762711193 (8)*



SKRF2.2WWLED
50,000 Hour
(7) 6762711196 (9)*



SKGCC2.2WWLED
50,000 Hour
(7) 6762711205 (8)*

LED SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Base	Lamp Life(Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
2.2	11191	SKCT2.2WWLED Candle Twist Crystal	15-25	33	E12	50,000	Box	48	1.4 x 4.2	2700
2.2	11204	SKCD2.2WWLED Candle Dimple Crystal	15-25	30	E12	50,000	Box	48	1.4 x 4.2	2700
2.2	11193	SKGC2.2WWLED Globe Clear/Outdoor	15-25	27	E26	50,000	Box	48	2 x 3.5	2700
2.2	11205	SKGCC2.2WWLED Globe Clear, E12/Outdoor	15-25	31	E12	50,000	Box	48	2 x 3.5	2700
2.2	11196	SKRF2.2WWLED R20 Frosted	15-25	22	E26	50,000	Box	48	2.5 x 4	2700

SPECIAL NOTES

- >> Designed especially for ambient lighting; where multi socket fixtures add to the beauty of a room
- >> Designed for low maintenance costs; with a lamp life of 50,000 hours (40% lumen depreciation)
- >> Fully compatible with timers and photo controls. Not for use with dimmers

APPLICATIONS

- Chandeliers
- Multi-socket fixtures (Marquees)
- Signage
- Wall Sconces
- Wall washing

LOCATIONS

- Hospitality
- Commercial Office
- Residential

BENEFITS

- True 2700K Color
- Super Long Life- 50,000 Hours
- 5 Year Warranty
- Available in clear and frosted glass
- Decorative shape and ultra-small size
- Very long maintenance cost

SPECIFICATIONS

- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

MAX11252-7-28

All specifications are subject to change without notice



FCC Certified
*UPC Codes

MaxLite™: 1-800-555-5629 Fax: 973-244-7300 info@maxlite.com www.maxlite.com

MaxLite West™: 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com