

PRODUCT FOCUS

MINIBULB

Compact Fluorescent Lamp

- FOR >>** TABLE , DESK & FLOOR LAMPS
 >> RECESSED LIGHTING
 >> WALL SCONCE
 >> CEILING MOUNTED LIGHTING
 >> TASK LIGHTING



SKB7EA★



SKB11EA★



SKB13EA ★
HCB13WW ★



SKB13EAPWW
SKB13EAPCW
SKB13EAPDL



SKB20EA★

★ ENERGY STAR® qualified



MAX11211-06-24

- Saves Energy – up to 75% savings
- Instant on, flicker free
- Familiar incandescent shape and small size fits most household fixtures
- Soft natural light with excellent color rendering

PRODUCT FOCUS **MINIBULB**
Compact Fluorescent Lamp



SKB7EAWW★
8,000 Hour
(7) 6762731131 (4)*



SKB11EAWW★
6,000 Hour
(7) 6762731132 (1)*



SKB13EAWW★
10,000 Hour
(7) 6762731533 (6)*



SKB13EAPWW
15,000 Hour
(7) 6762731531 (2)*



SKB20EAWW★
10,000 Hour
(7) 6762732032 (3)*

HCB13WW★
10,000 Hour
(7) 6762711578 (3)*

SKB13EAPCW
15,000 Hour
(7) 6762731535 (0)*

SKB13EAPDL
15,000 Hour
(7) 6762731534 (3)*

MINIBULBSPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 7	31131	SKB7EAWW A17 E26 Fan Light	25	450	10,000	Card	12	2.4 x 4.2	2700
★ 11	31132	SKB11EAWW A19 E26	40	500	10,000	Box	24	2.4 x 4.85	2700
★ 13	31533	SKB13EAWW A19 E26	60	800	10,000	Box	12	2.4 x 4.85	2700
★ 13	70240	HCB13WW6 A19 E26	60	800	10,000	Card	6	2.4 x 4.85	2700
13	70666	SKB13EAPWW A19 E26 Premium	60	800	15,000	Box	12	2.4 x 4.3	2700
13	31535	SKB13EAPCW A19 E26 Prem.	60	800	15,000	Box	12	2.4 x 4.3	4100
13	31534	SKB13EAPDL A19 E26 Premium	60	800	15,000	Box	12	2.4 x 4.3	5000
★ 20	70013	SKB20EAWW A21 E26	60	1050	10,000	Box	24	2.7 x 5.3	2700

SPECIAL NOTES

- >> Do not use with dimmers or other control devices.
- >> Suitable for indoor use.
- >> Fits most household fixtures.

APPLICATIONS

- Wall Sconces
- Recessed Lighting
- Table & Floor lamps

LOCATIONS

- Residential
- Restaurant
- Retail
- Hotel/Motel
- Office
- School/Hospital

BENEFITS

- Saves Energy – up to 75% savings
- Instant on, flicker free
- Familiar incandescent shape and small size fits most household fixtures
- Soft natural light with excellent color rendering

Premium MiniBulb

- UL Certified
- Same size as an incandescent A19
- Full brightness instantly

SPECIFICATIONS

- End of Life Ballast >> Yes
- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Operating Temp. >> 100°F
- Color Rendering Index >> 84

All specifications are subject to change without notice



FCC Certified
★ UPC Codes
★ ENERGY STAR®
Qualified



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.