

PRODUCT FOCUS

MINIGLOBE

Compact Fluorescent Lamp

- FOR >>**
- >> TABLE & FLOOR LAMPS
 - >> BATHROOM VANITY STRIPS
 - >> WALL SCONCE
 - >> HANGING PENDANT



SKM3EGC

SKM3EG

SKM7EG

SKM11EG★

SKM14EG 2700K★

SKM14EG 4100K

SKM14EG 5000K

★ ENERGY STAR® qualified



- Decorative shape and small size fits most fixtures
- Long life – lasts 8,000 Hours
- Saves up to 75% in energy costs
- Instant on, flicker free electronics
- Candelabra and Edison bases

MAX11071-03-8

PRODUCT FOCUS **MINIGLOBE**
Compact Fluorescent Lamp



SKM3EGWW
8,000 Hour
(7) 6762708003 (6)*



SKM3EGCWW
8,000 Hour
(7) 6762731003 (4)*



SKM7EGWW
8,000 Hour
(7) 6762708007 (4)*



SKM11EGWW★
10,000 Hour
(7) 6762708011 (1)*



SKM14EGWW★
8,000 Hour
(7) 6762731527 (5)*

SKM14EGCW
8,000 Hour
(7) 6762711147 (1)*

SKM14EGDL
8,000 Hour
(7) 6762731523 (7)*

MINIGLOBESPECIFICATIONS

All specifications are subject to change without notice

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
3	08003	SKM3EGWW G16 E26 Globe	20	135	8,000	Box	12	2 x 3.7	2700
3	31003	SKM3EGCWW G16 Globe E12 Base	20	135	8,000	Box	60	2 x 3.7	2700
7	08007	SKM7EGWW G20 E26 Globe	30	280	8,000	Box	12	2.4 x 4.3	2700
★ 11	08011	SKM11EGWW G20 E26 Globe	40	550	10,000	Box	12	2.76 x 4.65	2700
★ 14	31527	SKM14EGWW G25 E26 Globe	60	800	10,000	Box	12	3.1 x 4.4	2700
14	11147	SKM14EGCW G25 E26 Globe Cool White	60	900	8,000	Box	12	3.5 x 5.35	4100
14	31523	SKM14EGDL G25 E26 Globe Daylight	60	900	8,000	Box	12	3.5 x 5.35	5000

SPECIAL NOTES	APPLICATIONS	LOCATIONS
<ul style="list-style-type: none"> >> Do not use on circuits with dimmers, timers or other control devices >> Not for use in totally enclosed fixtures 	<ul style="list-style-type: none"> • Table & Floor Lamps • Bathroom Vanity Strips • Hanging Pendant & Wall Sconce 	<ul style="list-style-type: none"> • Residential • Restaurant • Retail • Office • School/Hospital • Hotel/Motel

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> • Decorative shape and small size fits most fixtures • Soft natural light with excellent color rendering • Long life – lasts 8,000 Hours • Saves Energy – up to 75% savings • Instant-on, flicker-free electronics • Candelabra and Edison bases 	<ul style="list-style-type: none"> • Ballast Type >> Electronic • Starting Method >> Instant Start • Input Line Voltage >> 120VAC • Input Line Frequency >> 50/60HZ • Mini. Starting Temp. >> 0°F • Max. Operating Temp. >> 100°F • Color Rendering Index >> 84

MAX11071-03-8

FC This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.

