

PRODUCT FOCUS **SENTRYMAX**

Compact Fluorescent Lamp
Outdoor Approved

**FOR >> OUTDOOR LAMPS
IN FIXTURES**

- >> POST LANTERNS
- >> CORRIDOR LIGHTING
- >> COVERED PORCH
OR BREEZEWAY

Anywhere that would benefit
from automatic on/off.

MAX11080-03-10
AUTOMATICALLY SWITCHES ON/OFF AT DUSK/DAWN
STANDING
GUARD TO
WELCOME
YOU HOME!



SKS20EP★

- Automatic Dusk-to-Dawn operation with advanced photo control
- Saves up to 75% in energy costs
Long life – lasts 8,000 hours
- Instant on, flicker free

PRODUCT FOCUS **SENTRYMAX**

Compact Fluorescent Lamp



SKS20EPWW★
8,000 Hour
(7) 6762714022 (8)★

SENTRYMAX SPECIFICATIONS

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 20	14022	SKS20EPWW Spiral w/ photocell	75	1300	8,000	Box	50	2.4 x 5.15	2700

SPECIAL NOTES	APPLICATIONS	LOCATIONS
<ul style="list-style-type: none"> >> Do not use with other photo controls. >> Automatic dusk-to-dawn operation means that you never come home to an unlighted house. 	<ul style="list-style-type: none"> • Outdoor Lamps in Fixtures • Corridor Lighting • Post Lanterns • Breezeway 	<ul style="list-style-type: none"> • Residential • Restaurant • Retail • Hotel/Motel • Office • School • Hospital

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> • Automatic Dusk-to-Dawn operation with advanced photocontrol • Saves Energy – up to 75% savings • Long Life – lasts 8,000 hours • Instant-on, flicker-free electronics • Soft natural light with excellent color rendering • No hassles with timers 	<ul style="list-style-type: none"> • Ballast Type >>> Electronic • Starting Method >>> Instant Start • Input Line Voltage >>> 120VAC • Input Line Frequency >>> 50/60HZ • Mini. Starting Temp. >>> 0°F • Max. Operating Temp. >>> 100°F • Color Rendering Index >>> 84

MAX11080-03-10

All specifications are subject to change without notice



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.



FCC Certified
ISO 9002 Certified
★ UPC Codes

MaxLite™: 1-800-555-5629 Fax: 973-244-7300 info@maxlite.com www.maxlite.com

MaxLite West™: 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com