



T2 Spirals

Compact Fluorescent Lamps

T2 Spiral SPECIFICATIONS

All specifications are subject to change without notice

Watts	Order Code	Description	Incandescent Equivalent	Lumens	Lamp Life (Hrs)	Pack Type	Case Pack	Dimensions (W" x MOL")	K
★ 9	70378	MLS9T2WW	40	550	10,000	Box	48	1.6 x 4.4	2700
9	70553	MLS9T2CW	40	550	10,000	Box	48	1.6 x 4.4	4100
★ 9	70545	MLS9T2DL	40	550	10,000	Box	48	1.6 x 4.4	5000
★ 9	N/A	SKS9T2WW	40	550	10,000	Box	48	1.6 x 4.4	2700
★ 9	N/A	SKS9T2CW	40	470	10,000	Box	48	1.6 x 4.4	4100
★ 9	N/A	SKS9T2DL	40	520	10,000	Box	48	1.6 x 4.4	5000
★ 11	N/A	MLS11T2WW	40	740	10,000	Box	48	1.63 x 4.4	2700
★ 13	70379	MLS13T2WW	60	900	10,000	Box	48	1.85 x 4.33	2700
★ 13	70924	SKS13T2WW	60	800	12,000	Box	48	1.8 x 4.1	2700
★ 13	70925	SKS13T2CW	60	880	12,000	Box	48	1.8 x 4.1	4100
★ 13	70554	MLS13T2CW	60	900	10,000	Box	48	1.85 x 4.33	4100
★ 13	70546	MLS13T2DL	60	900	10,000	Box	48	1.85 x 4.33	5000
★ 14	70593	MLS14T2WW	60	900	10,000	Box	48	1.87 x 4.33	2700
★ 14	70594	MLS14T2CW	60	830	10,000	Box	48	1.87 x 4.33	4100
★ 14	70595	MLS14T2DL	60	850	10,000	Box	48	1.87 x 4.33	5000
★ 18	70889	MLS18T2WW	75	1200	10,000	Box	96	2.15 x 4.55	2700
★ 19	70596	MLS19T2WW	75	1250	10,000	Box	48	2.2 x 4.49	2700
★ 20	70380	MLS20T2WW	75	1200	10,000	Box	48	2.2 x 4.49	4100
★ 20	70555	MLS20T2CW	75	1200	10,000	Box	48	2.2 x 4.49	4100
★ 20	70547	MLS20T2DL	75	1200	10,000	Box	48	2.2 x 4.49	5000
★ 23	70381	MLS23T2WW	100	1600	12,000	Box	48	2.3 x 4.4	2700
★ 23	70556	MLS23T2CW	100	1600	10,000	Box	48	2.32 x 5.12	4100
★ 23	70548	MLS23T2DL	100	1600	10,000	Box	48	2.32 x 5.12	5000
★ 23	70841	SKS23T2WW	100	1600	12,000	Box	48	2.1 x 4.9	2700
★ 23	70843	SKS23T2DL	100	1600	12,000	Box	48	2.1 x 4.9	5000
★ 26	N/A	MLS26T2WW	100	1700	10,000	Box	48	2.32 x 5.12	2700

SPECIAL NOTES	APPLICATIONS	LOCATIONS
>> Do not use on circuits with dimmers, timers or other control devices >> Not for use in totally enclosed fixtures	<ul style="list-style-type: none"> • Table & Floor Lamps • Recessed Light • Corridor Light & Wall Sconce 	<ul style="list-style-type: none"> • Residential • Restaurant • Retail • Office • School/Hospital • Hotel/Motel

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> • Ultra mini size fits most fixtures • Long life – lasts up to 10,000 hours • Saves Energy – up to 75% savings • Instant-on, flicker-free electronics 	<ul style="list-style-type: none"> • Ballast Type >> Electronic • Starting Method >> Instant Start • Input Line Voltage >> 120VAC • Input Line Frequency >> 50/60HZ • Mini. Starting Temp. >> 0°F • Max. Operating Temp. >> 100°F • Color Rendering Index >> 84

MAX11197-06-20



FCC Certified
 ★ UPC Codes
 ★ ENERGY STAR® Qualified



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.