



Energy Efficient Lighting Products

Model No.	SKE1324/SC
Ballast Type	Electronic
Lamp Operation	Parallel / Instant start
Input Voltage	120
Frequency	50/60hz

**SPECIFICATION**

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temperature (°F)	Lamp Current Crest Factor	B.E.F..
F32T8 32W	4	120	0.93	112	>0.98	<20%	0.88	0	1.7	0.79
F25T8 25W	4	120	0.74	89	>0.98	<20%	0.94	0	1.7	1.06
F17T8 17W	4	120	0.51	61	>0.98	<20%	0.96	0	1.7	1.57
F32T8/ES 25W	4	120	0.77	92	>0.98	<20%	0.88	0	1.7	0.96
F32T8/ES 28W	4	120	0.82	99	>0.98	<20%	0.88	0	1.7	0.89
F32T8/ES 30W	4	120	0.88	105	>0.98	<20%	0.88	0	1.7	0.84
F48T12 25W	4	120	0.78	93	>0.98	<20%	0.94	0	1.7	1.01
F48T12 34W	4	120	0.66	78	>0.98	<20%	0.60	0	1.7	0.77
F48T12 40W	4	120	0.78	92	>0.98	<20%	0.65	0	1.7	0.71
F40T8 40W	3	120	0.93	112	>0.98	<20%	0.88	0	1.7	0.79
F32T8 32W	3	120	0.79	94	>0.98	<20%	1.00	0	1.7	1.06
F25T8 25W	3	120	0.62	74	>0.98	<20%	1.04	0	1.7	1.41
F32T8/ES 25W	3	120	0.63	75	>0.98	<20%	1.00	0	1.7	1.33
F32T8/ES 28W	3	120	0.68	82	>0.98	<20%	1.00	0	1.7	1.22
F32T8/ES 30W	3	120	0.73	87	>0.98	<20%	1.00	0	1.7	1.15
F48T12 25W	3	120	0.58	70	>0.98	<20%	0.94	0	1.7	1.34
F48T12 34W	3	120	0.5	60	>0.98	<20%	0.60	0	1.7	1
F48T12 40W	3	120	0.63	75	>0.98	<20%	0.68	0	1.7	0.91

**Performance:**

- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class B (Consumer Limits)

**Safety:**

- No PCBs
- UL/CUL Listed
- Class P, Type 1 Outdoor
- OCV 600v

**Application:**

- Remote Mounting: 18 ft. Max. overall lead length, 18 AWG
- Maximum Case Temperature 75°C / 167° F
- Sound Rated - "A"
- Maximum Ambient Temperature 40°C / 105° F

Case	Inches
Length (L)	9.5
Width (W)	1.3
Height (H)	1
Mounting (M)	8.91
Weight (lbs.)	1.15

Lead Length	Inches (+/-1)
Black	25
White	25
Red	31
Blue	31
Yellow	46

