

WALL SCONCE

ML9 SERIES - LED INTEGRATED



Fleming



Architectural



Contemporary



PRODUCT DESCRIPTION:

The LED Wall Sconces provides long-lasting illumination with a decorative touch to corridors in hotels, motels and commercial property applications. They offer long life, high lumen maintenance, and dimmable operation for residential and commercial applications that exceed those of a traditional bulb fixture.

FEATURES:

- Flicker free
- Suitable for damp locations

CONSTRUCTION:

- Die formed steel
- Powder coat
- High transmission glass (Contemporary style) or Plastic (Architectural and Fleming style) lens

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

PRODUCT FAMILY	TYPE	STYLE	FINISH	OUTPUT	CCT/ CRI
ML9= Wall Sconces	LA= LED Integrated	F= Fleming, 12"	BN= Brushed Nickel	9= 9W	827= 2700K, 80 CRI
		17LCN= Contemporary, 8"		I = 17W	927= 2700K, 90 CRI
		R= Architectural, 10.5"		23= 23W	830= 3000K, 80 CRI

SPECIFICATIONS:

ORDER CODE: 77655
ML9LA17LCNBNI927

ORDER CODE: 1409631
ML9LARBN23830

ORDER CODE: 14099634
ML9LAFBN09827

ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Color Temperature (CCT)	2700K	2700K	2700K
	Delivered Lumens	1550 lm	1891 lm	685 lm
	Efficacy (lm/W)	88 lm/W	83 lm/W	71.1 lm/w
	Lumen Maintenance (L70)	50,000 Hrs		
ELECTRICAL	Input Voltage	120-277V, 50-60 Hz	120V, Triac dimming, 60Hz	120V, Triac dimming, 60Hz
	Power Consumption	17W	23W	9.7W
PHYSICAL	Dimensions	13.375" W x 7.875" H x 3" D	10.5"L x 9.4"W x 3.9"H	4.1"L x 5"W x 12"H
	Power Factor	>0.90		
	Operating Temperature	-4°F-113°F (-20°C-45°C)	-4°F to 104°F (-20°C - 40°C)	-4°F to 104°F (-20°C - 40°C)
CERTIFICATION	Certification	cULus, Energy Star, FCC	ETL, Energy Star, FCC	ETL, Energy Star, FCC
	Environment	Suitable for damp, install using only Class 2 power supply	Suitable for damp	Suitable for damp
	Warranty	5-year standard warranty*		