

ENHANCED

MLVT ArcMax Volumetric Panel

1x4	16W/20W/30W 1,968/2,460/3,690 lm	16W 1,978 lm
2x2	20W/30W/40W 2,460/3,690/4,920 lm	20W 2,554 lm
2x4	30W/40W/50W 3,690/4,920/6,150 lm	30W 3,756 lm



CMAX CR
CONTROLS COMPATIBLE



ENHANCED

TRK Troffer Retrofit Kit

1x4	20W/25W/30W 2,620/3,250/3,810 lm	
2x2	20W/25W/30W 2,660/3,250/3,810 lm	18W 2,471 lm
2x4	25W/30W/34W 3,325/3,900/4,320 lm	28W 3,510 lm



CMAX CR
CONTROLS COMPATIBLE



ENHANCED

Universal Downlight RRC Series

LIGHT ENGINES		REFLECTORS	OPTIONAL FRAMES
10W/15W/20W 1,046/1,476/1,944 lm	15W 1,480 lm	4", 6", 8" and 10"	4", 6", & 8"
20W/25W/30W 1,944/2,399/2,768 lm	25W 2,400 lm		

RETROFIT

NEW CONSTRUCTION



CMAX CR
CONTROLS COMPATIBLE



EFFICIENT

MLFP Flat Panel

1x4	30W/40W/50W 2,540/3,020/3,600 lm	
2x2	18W/27W/36W 2,000/2,900/3,820 lm	18W 2,000 lm
2x4	27W/36W/45W 3,140/4,090/4,920 lm	28W 3,100 lm




CMAX CR
CONTROLS COMPATIBLE



EFFICIENT

FPR Flat Panel Retrofit

30W 2,999 lm	30W 3,080 lm	40W 4,136 lm
1x4	2x2	2x4



EFFICIENT

Universal Downlight RCF Series Triac Dimming

4"	6"	6"	
9W	13W	18W	
750 lm	1,100 lm	1,650 lm	
8"	8"	8"	9.5"
13W	18W	22W	40W
1,115 lm	1,650 lm	2,120 lm	3,500 lm



CMAX CR
CONTROLS COMPATIBLE



LM Linear L-Max Luminaire

2FT	20W 2,570 lm	
4FT	40W 5,262 lm	60W 7,923 lm



MRBK Linear Magnetic Retrofit Bar

	LOW	MEDIUM	HIGH
2'	9W 1,125 lm	10W 1,130 lm	12W 1,575 lm
4'	12W 1,625 lm	14W 1,921 lm	18W 2,275 lm

AVAILABLE AS 1, 2, 3 OR 4 BAR KITS



Universal Downlight RCF Series 0-10V Dimming

4"	6"	8"
12W 900 lm	10W/12W/17W 1,000/1,200/17,000 lm	32W/42W/52W 3,200/4,000/5,000 lm
8"	9.5"	
14W/17W/20W 1,400/1,700/2,000 lm	30W/35W/40W 2,550/2,975/3,400 lm	



CMAX CR
CONTROLS COMPATIBLE



MaxLite®
A NEW WAVE OF LIGHT

INDUSTRIAL &
COMMERCIAL
LIGHTING GUIDE



12 York Ave.
West Caldwell, NJ 07006
T: 1-800-555-5629 F: 973-244-7333
www.maxlite.com

Round LED High Bays

ENHANCED

HPH High Temperature High Bay

240W
31,100 lm



EFFICIENT

BPHE2 Round ECO Pendant High Bay

90W/120W/150W
12,150/16,200/20,250 lm

180W/200W/240W
20,250/27,000/32,400 lm

100W
13,500 lm



AVAILABLE
IN BLACK



Linear LED High Bays

ENHANCED

HL3 High Bay Linear

1.5' 78W/92W/95W
11,700/13,800/15,750 lm

2' 135W 155W
20,250 lm 23,250 lm

4' 230W 270W
34,500 lm 40,500 lm



EFFICIENT

BLHE3 Linear Eco High Bay

2' 65W 85W 130W 170W
8,450 lm 11,475 lm 17,550 lm 22,950 lm

4' 210W 255W 300W 400W
28,350 lm 34,425 lm 40,500 lm 54,400 lm



LED Linear Fixtures

EFFICIENT

LSV Vapor Tight

2' 20W/25W/30W
2,600/3,250/3,900 lm

4' 23W/35W/48W
2,990/4,550/6,240 lm

8' 65W/75W/90W
8,450/9,750/11,700 lm



LSU Utility Wrap

2' 20W/25W/30W
2,600/3,250/3,900 lm

4' 23W/35W/48W
2,990/4,550/6,240 lm



LS2 Linear Strip

2' 20W/25W/30W
2,600/3,250/3,900 lm

4' 23W/35W/48W
2,990/4,420/6,110 lm

8' 65W/75W/90W
8,450/9,750/11,700 lm



LED Lamp Ready

EFFICIENT

T8/T5 LED Lamp Ready High Bay

4 Lamp 6 Lamp 8 Lamp



T8/T5 LED Lamp Ready Linear Strip

1 Lamp 2 Lamp



ENHANCED FAMILY

- Enhanced Performance and Features



EFFICIENT FAMILY

- Value Oriented Performance and Features



SCAN FOR FURTHER
DETAILS ONLINE



Controls Ready logo indicates easy in-field
Plug and Play sensor installation compatible
with Maxlite c-Max control system
(DLC NLC qualified)