Canopy & Parking

Residential and Security Lights



Enhanced Canopy/Parking Fixture

20W - 60W 2,490 - 8,370 lms











Dusk to Dawn Barn Lights

35 - 60W 4,730 - 7,850 lms





Oval & Slim GuardMax

15W - 30W 2,000 - 3,900 lms









Value CP Series

20W - 100W 2,500 - 12,500 lms















Residential Lanterns





Bollards



PathMax[™] Slim Bollard

17W - 22W 2,860 lm, 1,320 lm (louvers)













GuardMax Motion Sensor Security Light

1.7W





Jelly Jars











Using a patented, plug and play design, c-Max makes it easy to add luminaire-level lighting controls to achieve energy savings beyond LED conversion.





- Streamlined controls for essential needs
- Affordable in-fixture controls
- · Commission via remote control



- Bluetooth wireless NLC/LLLCsolution · Commission devices without needing
- Extensive range of indoor & outdoor sensors/nodes



- · Enhanced netword solutions with leading technology partners
- Agnostic to technology and connectivity prototcol
- Enable future IoT needs while meeting today's needs

Product Tiers





This series offers enhanced performance, features and options designed to elevate both safety and aesthetics in any outdoor environment.






This series combines reliable brightness, energy efficiency, and a budget-friendly price point, ensuring that users can enjoy effective outdoor lighting without compromising on quality.

MaxLite[®] **OUTDOOR** LIGHTING **GUIDE**



ITEM # OUTDOORBRO | ORDER CODE: 101165





M Series Floods

40W - 320W 5,300 - 47,930 lms























M Series Wall Mounts

40W - 320W 5,300 - 47,930 lms





M Series Area Lights

40W - 320W 5,300 - 47,930 lms

AE Switch & Remote Control Option

80W - 450W 9,470 - 63,520 lms



PROGRESS REPORT 2025 SELECTION



Square/Round Poles & Mounting Accessories

8' - 30' Steel or Aluminum



Emergency/Exit Lights



























Exit/Emergency Fixtures

UL924 Wet Location

















Slim Floods/Adjustable Beam

15W - 320W

FieldMax[™]HO Flood

520 - 1200W 77,350 - 172, 050 lms







Bullet Floods

9 - 25W 1,180 - 3,320 lms













Wall Lights



WallMax[™] Thin Cutoff

15-120W 2.150 - 16.400 lm





WallMax[™] Compact Open Face

29 - 120W 3,500 - 17,500 lms



















WallMax[™] Cutoff

15W - 100W

2.100 - 13.500 lms







WallMax[™] Open Face Face

28 - 120W 3,300 - 14,000 lms























