

Which downlight will work best for your project?

MaxLite[®]



RCF
LED Universal Downlights



RRECO
LED Commercial Downlight
Retrofits Economical Series



RRC
LED Commercial Downlight Retrofits

Retrofit?	Yes		Yes		Yes			
Fixture?	Yes		Yes w/ frame accessory		Yes w/ frame accessory			
Nominal Size	6"	8"	6"	8"	4"	6"	8"	9"
Wattages/ Nominal Lumens	13W/1300 lm, 18W/1800 lm	13W/1400 lm, 18W/1900 lm	12W/950 lm, 18W/1400 lm, 27W/2200 lm	12W/1000 lm, 18W/1500 lm, 24W/2000 lm, 40W/3300 lm	10W/900 lm, 15W/1250 lm	10W/900 lm, 15W/1250 lm, 20W/1800 lm	10W/900 lm, 15W/1250 lm, 20W/1800 lm, 30W/2800 lm, 50W/4400 lm	10W/900 lm, 15W/1250 lm, 20W/1800 lm, 30W/2800 lm, 50W/4400 lm
CCT	3000K, 3500K, 4000K		3000K, 4000K		3000K, 3500K, 4000K			
CRI*	≥80		≥80		≥80			
Voltage	120-277V		120-277V		120-277V			
Dimming	Triac (120V only)		0-10V		0-10V, Triac (120V only)			
EM Option	Iota IIS-35-HE Compatible <small>(Not sold by MaxLite)</small>		EBUDV487D145A <small>(Sold Separately)</small>		Integrated Emergency Backup			
Rating	Non-IC/Damp		Non-IC/Damp		IC/Non-IC/Damp			
Safety Certifications	ETL Classified, ETL Listed		UL Classified		UL Classified			
Certifications	Energy Star		Energy Star		Energy Star			
L70	50,000 Hours		50,000 Hours		50,000 Hours			
Warranty	5 Years		5 Years		5 Years			
Accessories	None		Frames, Trim Extender		Frames, Trim Extender			

* High CRI available by special order

Which downlight will work best for your project?



Downlight Selection Guide

Ceiling Height	Lumens	Equivalencies	4"	6"	8"	9"
8'-20'	1000 ± 250	MH - 50W CFL - 18W, 26W, 32W	RRXC10U## + RRC4-RFL	RRXC10U## + RRC6-RFL RRECO612##W/V2	RRXC10U## + RRC8-RFL RRECO812##W/V2	RRXC10U## + RRC9-RFL
	1500 ± 250	INC. - 65W BR30, 120W BR40, 150W A21	RRXC15U## + RRC4-RFL	RRXC15U## + RRC6-RFL RRECO618##W/V2 RCF613##W	RRXC15U## + RRC8-RFL RRECO818##W/V2 RCF813##W	RRXC15U## + RRC9-RFL
20'-30'	2000 ± 250	MH - 70W CFL - 2/26W, 1/42W, 1/57W, 2/32W		RRXC20U## + RRC6-RFL RRECO627##W/V2 RCF618##W	RRXC20U## + RRC8-RFL RRECO824##W/V2 RCF818##W	RRXC20U## + RRC9-RFL
	2500 ± 250	INC. - 200W A21				
30'-40'	3000 ± 250				RRXC30U## + RRC8-RFL RRECO840##W/V2	RRXC30U## + RRC9-RFL
	3500 ± 250	MH - 70W, 100W CFL - 3/26W, 3/32W, 2/42W, 3/42W, 2/57W				
	4000 ± 250	INC. - 300W BR40				
	4500 ± 250				RRXC50U## + RRC8-RFL	RRXC50U## + RRC9-RFL